



Une traçabilité fiable
Reliable traceability

LiveTrack[®] RFID Reader Bluetooth[®]

Used globally by Wild Life Research and Conservation Organizations, the LiveTrack[®] reader is the most advanced and affordable ISO hand held wand reader. With a memory of up to 10,000 RFID tags, the LiveTrack[®] reader is **robust and easy to use**, making it an ideal solution for reading **PIT** tags at tagging sites. Since the LiveTrack[®] is integrated with Bluetooth, it makes reading and transmitting **PIT** tags to the laptop trouble free up to 300 feet away.

Technical Data

Case:	Polycarbonate ABS
Operating Frequency:	125.0 kHz, 134.2 kHz
RFID Compatibility:	ISO HDX, ISO FDX-B, Industrial HDX
Reading Distance:	25-35 cm, 10-14 Inches
Memory:	10, 000 tags
Communication Ports:	Serial RS232 or optional Bluetooth (Class1, 100m)
Battery Power:	7.4V Li-ion rechargeable
Power Input:	12 VDC for charging the battery
Protection Class:	IP 66
Dimensions:	65 X 10 X 3cm 26 x 4 x 1.2"
Weight:	0.7 kg or 1.5 lbs
Display:	"OLED" 126 x 64 pixels
Display Languages:	English, French, Spanish
Certifications:	IC, FCC, CE, C-Tick
Included in the box:	Quick Start Guide, Reader, LiveTrack [®] Manager Software CD, Manual, Hand Strap, Serial Cable and 12v DC international power supply



LiveTrack[®] Manager Software

Out of the box tracking solution

Reader's Info

ID: **LIVETRACK I80-LTL03146**
 Firmware: **VF05.16r 2008-11-05**
 Temperature: **00 Celsius**
 Battery: **7.51 Volts**
 Date: **2009-02-25**
 Time: **09:50:51** [Synchronize]

Memory
 Number of Tags: **00245**
 [Download] [Erase]

Counter
 Tag Counter: **00233**
 [Reset]

String Format
 Tag Type Tag ID Scan Time Scan Site [Save]
FCCDDDDDDDDDDDAASSMMHHWDDMMYYTTTTTTT [?]

Settings
 Language: French [Save]
 Site Number: 1453409 [Save]
 Allow Duplicates in Reader
 Continuous Read Vibrator
 Single Read Buzzer

Turn Off Delays
 Delays from 30 to 9999 (Sec)
 Bluetooth: 0120
 Antenna: 0060
 Reader: 0120
 [Save]

Bluetooth Master/Slave
 000000000000 **Current: Slave**
 [Master] [Slave]

Type	Tag ID	Date	Time	Site #
F	124000312959256	30-12-2008	12:54:25	145340
F	124000313257363	30-12-2008	12:54:37	145340
F	124000312959301	30-12-2008	12:54:44	145340
F	124000312959251	30-12-2008	12:54:56	145340
F	124000312099628	30-12-2008	12:55:21	145340
F	124000312959303	30-12-2008	12:55:27	145340
F	124000312099608	30-12-2008	12:55:34	145340
F	124000313257362	30-12-2008	12:55:42	145340
F	124000312507694	30-12-2008	12:55:57	145340
O	000000000000000	30-12-2008	13:16:00	145340
F	124000313031506	30-12-2008	13:16:23	145340
F	124000313031523	30-12-2008	13:16:35	145340
F	124000313031512	30-12-2008	13:16:41	145340
F	124000313031557	30-12-2008	13:16:46	145340
F	124000313031562	30-12-2008	13:16:52	145340
F	124000313031514	30-12-2008	13:17:00	145340
F	124000313031564	30-12-2008	13:17:09	145340
F	124000313031516	30-12-2008	13:17:13	145340
F	124000313031540	30-12-2008	13:17:18	145340
F	124000313031516	30-12-2008	13:17:27	145340
F	124000313031527	30-12-2008	13:17:32	145340

[Save Log] [Clear Log] **00245**
 .CSV .TXT Remove Duplicates in Log

[Reset to Default Settings]

Advantages

- ISO 11784 and 11785 compliance
- Reads HDX and FDX-B and Industrial DX
- Light weight, ergonomic design
- Robust construction
- Read confirmation via vibration and sound
- Best graphic visibility
- Water Proof/Air tight
- Easy battery exchange
- Includes international power supply
- Languages: English, French and Spanish
- Simple PC/Laptop configuration
- Contact Syscan for other Livestock traceability solutions to fit your needs



SYSCAN-ID Inc.
 1975 Hymus, suite 225
 Dorval, QC H9P 1J8 CANADA
 Tel. 1 514 685 7778
 Fax 1 514 685 1938
www.syscan.com or sales@syscan-id.com